DAYCON Landers in Facility Maintenance Bulliston

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 1: IDENTIFICATION

1.1 Product identifier: SDS288 - FAST BREAK Wood Floor Coatining

Other means of identification:

Item No. (Gal.): 157870

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses (Consumer use):

- Product for protecting floors

Relevant uses (Professional users):

- Product for protecting floors

Relevant Uses: (Professional, Consumer)

Coating for wood floors. Best performance when applied to sanded wood floors.

Gym floor coating.

Racquetball Court Floor Coating.

Residential and apartment wood floor coating.

Best application method is a weighted bar applicator such as the Padco Applicator with short nap.

Uses advised against:

- All uses not specified in this section or in section 7.3

1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:

Daycon Products Company, Inc. 16001 Trade Zone Avenue

20774 Upper Marlboro - Maryland - United States

Phone: 800-394-0019 cswensen@daycon.com www.daycon.com

1.4 Emergency phone number: INFOTRAC: 01-800-535-5053

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

29 CFR 1910.1200:

Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200

Repr. 2: Reproductive toxicity, Category 2, H361

2.2 Label elements:

29 CFR 1910.1200:

Warning



Hazard statements:

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P280: Wear protective gloves/protective clothing/eye protection/protective footwear.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P405: Store locked up.

P501: Dispose of the contents/containers according to the local, state and federal regulations.

Substances that contribute to the classification

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate

Additional labeling:

DAYCON Leaders in Facility Maintenance Builtion

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 2: HAZARD(S) IDENTIFICATION (continued)



WARNING

Keep out of the reach of children

Federal Hazardous Substances Act (FHSA) >> Chronic toxicity (Reproductive Toxicants)

May damage fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep out of reach of children. Store locked up.

FIRST AID TREATMENT

IF exposed or concerned: Get medical advice/attention.

Contains: 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate.

This product can expose you to chemicals including 1,4-dioxane, which is [are] known to the State of California to cause cancer, and Ethanediol, 2-ethoxyethanol, Ethanediol, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

2.3 Hazards not otherwise classified (HNOC):

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Aqueous dispersion of acrylic copolymer

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 6846-50-0	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate Repr. 2: H361 - Warning		<1 %
CAS: 126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol Eye Dam. 1: H318; Skin Sens. 1B: H317 - Danger	(1)	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or shower the person affected if necessary thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS of this product.

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 2/11**

DAYCON Leaders in Facility Maintenance Builtion

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 4: FIRST-AID MEASURES (continued)

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportables quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 3/11**

DAYCON

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Identification Occupational exposure limits		
1,4-dioxane	8-hour TWA PEL	100 ppm	360 mg/m ³
	Ceiling Values - TWA PEL		
2-ethoxyethanol (1)	8-hour TWA PEL	200 ppm	740 mg/m ³
	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		mits
1,4-dioxane	TLV-TWA	20 ppm	
CAS: 123-91-1	TLV-STEL		
Ethanediol (1)	TLV-TWA		10 mg/m ³
CAS: 107-21-1	TLV-STEL		20 mg/m ³
2-ethoxyethanol (1)	TLV-TWA	5 ppm	
CAS: 110-80-5	TLV-STEL		
Ethanediol (1)	TLV-TWA		10 mg/m ³
CAS: 107-21-1	TLV-STEL		20 mg/m ³

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occu	Occupational exposure limits		
1,4-dioxane	PEL	0.28 ppm	1 mg/m³	
CAS: 123-91-1	STEL			

(1) Skin

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 4/11**

DAYCON Leaders in Facility Maintenance Bellution

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
Ethanediol (1)	PEL	40 ppm	100 mg/m ³
CAS: 107-21-1	STEL		
2-ethoxyethanol (1)	PEL	5 ppm	18 mg/m ³
CAS: 110-80-5	STEL		
Ethanediol (1)	PEL	40 ppm	100 mg/m ³
CAS: 107-21-1	STEL		

NIOSH: Immediately Dangerous To Life or Health (IDLH) Values:

Identification	Occupational exposure limits		
1,4-dioxane	TWA		
CAS: 123-91-1	IDLH Value	500 ppm	
2-ethoxyethanol (1)	TWA		
CAS: 110-80-5	IDLH Value	500 ppm	

⁽¹⁾ Skin

Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
2-ethoxyethanol CAS: 110-80-5	100 mg/g (Creatinine)	2-Ethoxyacetic acid in urine	End of shift at end of workweek

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

If the working conditions and/or safety measures adopted do not allow keeping the airborne concentration of the product below the exposure limits (if any) or at acceptable levels (if no exposure limits exist), suitable respiratory protection equipment chosen by a qualified professional should be used.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional /industrial users, we recommend using chemical protection gloves. Use gloves in accordance with manufacturer

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration.

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 5/11**



Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Remarks
	Anti-slip work shoes	Replace before any evidence of deterioration.

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
4	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	0+	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

40 CFR Part 59 (VOC):

V.O.C.(weight-percent): 7.08 % weight

V.O.C. at 68 °F: 194.91 kg/m³ (194.91 g/L) California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent): 7.08 % weight

V.O.C. at 68 °F: 194.91 kg/m³ (194.91 g/L)

South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent): 7.08 % weight

V.O.C. at 68 °F: 194.91 kg/m³ (194.91 g/L)

Ozone Transport Commission (OTC) Rules - VOC Regulatory:

V.O.C.(weight-percent): 7.08 % weight

V.O.C. at 68 °F: 194.91 kg/m³ (194.91 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F:

Appearance:

Color:

White

Odor:

Ammoniacal

Odour threshold:

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 227 °F Vapour pressure at 68 °F: 2309 Pa

Vapour pressure at 122 °F: 12166.36 Pa (12.17 kPa)

Evaporation rate at 68 °F: Non-applicable *

Product description:

Density at 68 °F: 1044.6 kg/m³

Relative density at 68 °F: 1.045

*Non-applicable due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 6/11**

DAYCON Landers in Facility Maintenance Bulliston

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Dynamic viscosity at 68 °F:

Kinematic viscosity at 68 °F:

Kinematic viscosity at 104 °F:

Concentration:

PH:

≈8.3 - 9.1

Vapour density at 68 °F:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Solubility in water at 68 °F:

Solubility properties:

Non-applicable *

Non-applicable *

Non-applicable *

Melting point/freezing point:

Non-applicable *

Flammability:

Flash Point: 205 °F

Flammability (solid, gas):

Non-applicable *

Autoignition temperature: 399 °F

Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable components:

Non-applicable *

Non-applicable *

Other safety characteristics:

Surface tension at 68 °F:

Refraction index:

Non-applicable *

Non-applicable *

*Non-applicable due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and fr	iction (Contact with air	Increase in temperature	Sunlight	Humidity
Not applica	ble	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 7/11**



Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: 1,4-dioxane (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected of damaging fertility or the unborn child
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

DAYCON Leaders in Facility Maintenance Builtion

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	LD50 oral	>5000 mg/kg	Rat
CAS: 6846-50-0	LD50 dermal		
	LC50 inhalation		
	LC50 inhalation vapour		

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration		Species	Genus
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 6846-50-0	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
2,4,7,9-tetramethyldec-5-yne-4,7-diol	LC50	>10 - 100 mg/L (96 h)		Fish
CAS: 126-86-3	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 6846-50-0	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	39 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	BCF	1
CAS: 6846-50-0	Pow Log	4.1
	Potential	Low

12.4 Mobility in soil:

Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste (Title 40 of the Code of Federal Regulations Part 261.4)

Waste management (disposal and evaluation):

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 9/11**

DAYCON Leaders in Facility Maintenance Solution

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE The Hazardous Substances List: 1,4-dioxane (123-91-1); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Birth defects or other reproductive harm: Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ethanediol (107-21-1)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Cancer: 1,4-dioxane (123-91-1)
- CANADA-Domestic Substances List (DSL): Water (7732-18-5); 5-chloro-2-methyl-2H-isothiazol-3-one (26172-55-4); 2-methylisothiazol-3(2H)-one (2682-20-4); Magnesium chloride (7786-30-3); Alcohols, C10-16, ethoxylated, sulfates, sodium salts (68585-34-2); 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (6846-50-0); Tris(2-butoxyethyl) phosphate (78-51-3); 2,4,7,9-tetramethyldec-5-yne-4,7-diol (126-86-3); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6) CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Reportable Quantities: 1,4-dioxane (123-91-1) U108; 2-(2-ethoxyethoxy)ethanol (111-90-0) 1 lb; Ethanediol (107-21-1) 5000 lb; 2-ethoxyethanol (110-80-5) U359; Ethanediol (107-21-1) NULL 5000 kg; Ammonia 10 25 %, aqueous solution (1336-21-6) 1000 lb
- Hazardous Air Pollutants (Clean Air Act): 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); Ethanediol (107-21-1)
- Massachusetts RTK Substance List: 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6)
- Minnesota Hazardous substances ERTK: 1,4-dioxane (123-91-1); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ethanediol (107-21-1)
- New Jersey Worker and Community Right-to-Know Act: 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6)
- New York RTK Substance list: 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6)
- NTP (National Toxicology Program): 1,4-dioxane (123-91-1)
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0)
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: 5-chloro-2-methyl-2H-isothiazol-3-one (26172-55-4); Magnesium chloride (7786-30-3); 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Tris(2-butoxyethyl) phosphate (78-51-3); 2,4,7,9-tetramethyldec-5-yne-4,7-diol (126-86-3); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6)
- Rhode Island Hazardous substances RTK: 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ammonia 10 25 %, aqueous solution (1336-21-6)
- SB-258 Cleaning Product Right to Know Act: 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Tris(2-butoxyethyl) phosphate (78-51-3); Ethanediol (107-21-1)
- The Toxic Substances Control Act (TSCA): Water (7732-18-5); 5-chloro-2-methyl-2H-isothiazol-3-one (26172-55-4); 2-methylisothiazol-3(2H)-one (2682-20-4); Magnesium chloride (7786-30-3); Alcohols, C10-16, ethoxylated, sulfates, sodium salts (68585-34-2); 1,4-dioxane (123-91-1); 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate (6846-50-0); Tris(2-butoxyethyl) phosphate (78-51-3); 2,4,7,9-tetramethyldec-5-yne-4,7-diol (126-86-3); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6)
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): 1,4-dioxane (123-91-1);
- 2-(2-ethoxyethoxy)ethanol (111-90-0); Ethanediol (107-21-1); 2-ethoxyethanol (110-80-5); Ethanediol (107-21-1); Ammonia 10 25 %, aqueous solution (1336-21-6)

DAYCON Landers in Facility Maintenance Bulliston

Safety data sheet according to 29 CFR 1910.1200

SDS288 - FAST BREAK Wood Floor Coatining



Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1)

SECTION 15: REGULATORY INFORMATION (continued)

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

Other information:

All ingredients in the product formula are on the TSCA Inventory.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H361: Suspected of damaging fertility or the unborn child.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:

Eye Dam. 1: H318 - Causes serious eye damage.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon IARC: International Agency for Research on Cancer

NFPA:

Health Hazards: 0 Flammability Hazards: 1 Instability Hazards: 0

Date of compilation: 8/5/2025

0 0

Special Hazards: Non-applicable

Revised: 8/5/2025

Information in this Safety Data Sheet (SDS) is based on sources other than direct test data and is given in good faith. No warranty is expressed or implied. We believe that the information is current as of the date of this SDS. The use of this information, the conditions, the methods of handling, storage, use and disposal of the product are not within the control of the manufacturer and distributor, therefore it is the user's responsibility and obligation to determine the conditions of the safe use of this product and to ensure that its activities comply with all laws and regulations.

END OF SAFETY DATA SHEET

Printing: 8/5/2025 Date of compilation: 8/5/2025 Revised: 8/5/2025 Version: 2 (Replaced 1) **Page 11/11**