



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

**SECTION 1: IDENTIFICATION****1.1 Product identifier:** SDS433

- METEOR Floor Finish Remover

**Other means of identification:**

Item Number (Gallon): 415018

Item Number (5 Gallon): METEOR5GAL

**1.2 Recommended use of the chemical and restrictions on use:**

Relevant uses (Professional users):

- Alkaline floor stripper

For Professional users only.

Relevant Use (Professional):

Acrylic and Urethane Floor Finish Stripper

Degreaser

Heavy Duty Cleaner

Concrete Cleaner

Uses advised against:

- All uses not specified in this section or in section 7.3

**1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:**

Daycon Products Company, Inc.

16001 Trade Zone Avenue

20774 Upper Marlboro - Maryland - United States

Phone: 800-394-0019

cswensen@daycon.com

www.daycon.com

**1.4 Emergency phone number:** INFOTRAC: 01-800-535-5053**SECTION 2: HAZARD(S) IDENTIFICATION****2.1 Classification of the substance or mixture:****29 CFR 1910.1200:**

Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1B: Skin corrosion, Category 1B, H314

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

**2.2 Label elements:****29 CFR 1910.1200:**

Danger

**Hazard statements:**

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

STOT SE 3: H335 - May cause respiratory irritation.

**Precautionary statements:**

P280: Wear protective gloves/protective clothing/eye protection/protective footwear.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a poison center/doctor.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 2: HAZARD(S) IDENTIFICATION (continued)

### Substances that contribute to the classification

2-aminoethanol; Alcohol ethoxylated (C9-C11); N,N-dimethyl dec-9-enamide; Dodecylbenzenesulphonic acid, compound with 2-aminoethanol (1:1)

### Additional labeling:



#### WARNING

Keep out of the reach of children

This product can expose you to chemicals including 2,2'-iminodiethanol, which is [are] known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### 2.3 Hazards not otherwise classified (HNOC):

Non-applicable

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances:

Non-applicable

### 3.2 Mixtures:

**Chemical description:** Aqueous solution based on alkali silicates, glycol-ethers, surfactants and colourants.

#### Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 7732-18-5	<b>Water</b>	50 - <75%
CAS: 106463-17-6	<b>(-)-(R)-5,4,2-[2-(O-ethoxyphenoxy ) ethyl]amino-propyl-2-methoxybenzenesulfonamide hydrochloride</b> Acute Tox. 4: H302 - Warning	10 - <25%
CAS: 1356964-77-6	<b>N,N-dimethyl dec-9-enamide</b> Acute Tox. 4: H302; Eye Irrit. 2A: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	2.5 - <10%
CAS: 68439-46-3	<b>Alcohol ethoxylated (C9-C11)</b> Acute Tox. 4: H302; Eye Dam. 1: H318 - Danger	2.5 - <10%
CAS: 26836-07-7	<b>Dodecylbenzenesulphonic acid, compound with 2-aminoethanol (1:1)</b> Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger	2.5 - <10%
CAS: 141-43-5	<b>2-aminoethanol</b> Acute Tox. 4: H302+H312+H332; Flam. Liq. 4: H227; Skin Corr. 1B: H314 - Danger	3 - <6%
CAS: 764-71-6	<b>potassium octanoate</b> Eye Irrit. 2A: H319; Skin Irrit. 2: H315 - Warning	1 - <2.5%
CAS: 334-48-5	<b>Decanoic acid</b> Eye Irrit. 2A: H319; Skin Irrit. 2: H315 - Warning	1 - <2.5%
CAS: 61789-30-8	<b>Fatty acids, coco, potassium salts</b> Eye Irrit. 2A: H319; Skin Irrit. 2: H315 - Warning	1 - <2.5%
CAS: 5324-84-5	<b>Sodium octane-1-sulphonate monohydrate</b> Eye Irrit. 2A: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	1 - <2.5%
CAS: 6132-04-3	<b>Sodium citrate · 2H2O</b>	1 - <2.5%
CAS: 103-50-4	<b>Dibenzyl ether</b> Skin Sens. 1B: H317 - Warning	<1%
CAS: 67-63-0	<b>propan-2-ol</b> Eye Irrit. 2A: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	<1%

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)**

There is less than 6% excess 2-aminoethanol in this product. Any excess 2-aminoethanol and the ((-)-(R)-5,4,2-[2-(O-ethoxyphenoxy)ethyl]amino-propyl-2-methoxybenzenesulfonamide hydrochloride) react to form Monoethanolamine Dodecyl Sulfonate.

**SECTION 4: FIRST-AID MEASURES****4.1 Description of necessary measures:**

Request medical assistance immediately, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and its inhalation, to the respiratory system. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Keep the person affected at rest.

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Non-applicable

**SECTION 5: FIRE-FIGHTING MEASURES****5.1 Suitable (and unsuitable) extinguishing media:****Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

**Unsuitable extinguishing media:**

Non-applicable

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

### 6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportables quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

#### A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

#### B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

#### C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

#### D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

#### A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

Maximum time: 12 Months

#### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits	
2-aminoethanol <sup>(1)</sup> CAS: 141-43-5	8-hour TWA PEL Ceiling Values - TWA PEL	3 ppm 6 mg/m <sup>3</sup>
sodium hydroxide CAS: 1310-73-2	8-hour TWA PEL Ceiling Values - TWA PEL	2 mg/m <sup>3</sup>
propan-2-ol CAS: 67-63-0	8-hour TWA PEL Ceiling Values - TWA PEL	400 ppm 980 mg/m <sup>3</sup>

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits	
2-aminoethanol <sup>(1)</sup> CAS: 141-43-5	TLV-TWA TLV-STEL	3 ppm 6 ppm
2,2'-iminodiethanol CAS: 111-42-2	TLV-TWA TLV-STEL	2 mg/m <sup>3</sup>
sodium hydroxide CAS: 1310-73-2	TLV-TWA TLV-STEL	2 mg/m <sup>3</sup>
propan-2-ol CAS: 67-63-0	TLV-TWA TLV-STEL	200 ppm 400 ppm

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	Occupational exposure limits		
2-aminoethanol <sup>(1)</sup> CAS: 141-43-5	PEL STEL	3 ppm 6 ppm	8 mg/m <sup>3</sup> 15 mg/m <sup>3</sup>
2,2'-iminodiethanol CAS: 111-42-2	PEL STEL	0.46 ppm	2 mg/m <sup>3</sup>
sodium hydroxide CAS: 1310-73-2	PEL STEL		2 mg/m <sup>3</sup>
propan-2-ol CAS: 67-63-0	PEL STEL	400 ppm 500 ppm	980 mg/m <sup>3</sup> 1225 mg/m <sup>3</sup>

NIOSH: Immediately Dangerous To Life or Health (IDLH) Values:

Identification	Occupational exposure limits		
2-aminoethanol <sup>(1)</sup> CAS: 141-43-5	TWA IDLH Value	30 ppm	
sodium hydroxide CAS: 1310-73-2	TWA IDLH Value		10 mg/m <sup>3</sup>
propan-2-ol CAS: 67-63-0	TWA IDLH Value	2000 ppm	

<sup>(1)</sup> Skin

### Biological limit values:

Biological Exposure Indices (BEIs®) - ACGIH

Identification	BEIs®	Determinant	Sampling Time
propan-2-ol CAS: 67-63-0	40 mg/L	Acetone in urine	End of shift at end of workweek

### 8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

### B.- Respiratory protection

If the working conditions and/or safety measures adopted do not allow keeping the airborne concentration of the product below the exposure limits (if any) or at acceptable levels (if no exposure limits exist), suitable respiratory protection equipment chosen by a qualified professional should be used.

### C.- Specific protection for the hands

Pictogram	PPE	Remarks
	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

### D.- Eye and face protection

Pictogram	PPE	Remarks
	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

### E.- Bodily protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration.
	Anti-slip work shoes	Replace before any evidence of deterioration.

### F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011		DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

### Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

### 40 CFR Part 59 (VOC):

V.O.C.(weight-percent): 5.96 % weight  
V.O.C. at 68 °F: 164.8 kg/m<sup>3</sup> (164.8 g/L)

### California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent): 5.96 % weight

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. at 68 °F: 164.8 kg/m<sup>3</sup> (164.8 g/L)

### South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent): 5.96 % weight

V.O.C. at 68 °F: 164.8 kg/m<sup>3</sup> (164.8 g/L)

### Ozone Transport Commission (OTC) Rules - VOC Regulatory:

V.O.C.(weight-percent): 5.96 % weight

V.O.C. at 68 °F: 164.8 kg/m<sup>3</sup> (164.8 g/L)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 68 °F: Liquid

Appearance: Transparent

Color: Red

Odor: Solvent

#### Volatility:

Boiling point at atmospheric pressure: 226 °F

Vapour pressure at 68 °F: 2277 Pa

Vapour pressure at 122 °F: 11998.48 Pa (12 kPa)

Evaporation rate at 68 °F: Non-applicable \*

#### Product description:

Density at 68 °F: 1011.5 kg/m<sup>3</sup>

Relative density at 68 °F: 1.012

Dynamic viscosity at 68 °F: Non-applicable \*

Kinematic viscosity at 68 °F: Non-applicable \*

Kinematic viscosity at 104 °F: Non-applicable \*

Concentration: >30 g/L (active ingredient)

pH: ≈10 - 11.3

Vapour density at 68 °F: Non-applicable \*

Partition coefficient n-octanol/water 68 °F: Non-applicable \*

Solubility in water at 68 °F: Non-applicable \*

Solubility properties: Non-applicable \*

Decomposition temperature: Non-applicable \*

Melting point/freezing point: Non-applicable \*

#### Flammability:

Flash Point: 204 °F

Flammability (solid, gas): Non-applicable \*

Autoignition temperature: 377 °F

Lower flammability limit: Non-applicable \*

Upper flammability limit: Non-applicable \*

#### Particle characteristics:

Median equivalent diameter: Non-applicable \*

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

### 9.2 Other information:

#### Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

#### Other safety characteristics:

Surface tension at 68 °F:	Non-applicable *
Refraction index:	Non-applicable *
MIR (Maximum Incremental Reactivity):	0.4
pH (Diluted 1:5) = 10.0 - 10.8	

\*Non-applicable due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

##### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

##### B- Inhalation (acute effect):

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.

- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: 2,2'-iminodiethanol (2B: Possibly carcinogenic to humans); propan-2-ol (3: Not classifiable as to its carcinogenicity to humans)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
2-aminoethanol CAS: 141-43-5	LD50 oral	1089 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	11 mg/L	
(-)-(R)-5,4,2-[2-(O-ethoxyphenoxy) ethyl]amino-propyl-2-methoxybenzenesulfonamide hydrochloride CAS: 106463-17-6	LD50 oral	500 mg/kg	
	LD50 dermal		
	LC50 inhalation dust		
Decanoic acid CAS: 334-48-5	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation dust		
N,N-dimethyl dec-9-enamide CAS: 1356964-77-6	LD50 oral	550 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		
Alcohol ethoxylated (C9-C11) CAS: 68439-46-3	LD50 oral	1400 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
Dibenzyl ether CAS: 103-50-4	LD50 oral	2500 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		
propan-2-ol CAS: 67-63-0	LD50 oral	>5840 mg/kg	Rat
	LD50 dermal	>13900 mg/kg	Rabbit
	LC50 inhalation vapour	>25 mg/L (6 h)	Rat

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### 12.1 Ecotoxicity (aquatic and terrestrial, where available):

#### Acute toxicity:

Identification	Concentration	Species	Genus
2-aminoethanol CAS: 141-43-5	LC50 349 mg/L (96 h)	Cyprinus carpio	Fish
	EC50 65 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 22 mg/L (72 h)	Scenedesmus subspicatus	Algae
N,N-dimethyl dec-9-enamide CAS: 1356964-77-6	LC50 14.8 mg/L (96 h)	Brachydanio rerio	Fish
	EC50 2.8 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 7.2 mg/L (96 h)	Pseudokirchneriella subcapitata	Algae
Alcohol ethoxylated (C9-C11) CAS: 68439-46-3	LC50 113 mg/L (96 h)	QSAR	Fish
	EC50 Non-applicable		
	EC50 Non-applicable		
Decanoic acid CAS: 334-48-5	LC50 >10 - 100 mg/L (96 h)		Fish
	EC50 >10 - 100 mg/L (48 h)		Crustacean
	EC50 >10 - 100 mg/L (72 h)		Algae
Dibenzyl ether CAS: 103-50-4	LC50 >0.1 - 1 mg/L (96 h)		Fish
	EC50 >0.1 - 1 mg/L (48 h)		Crustacean
	EC50 >0.1 - 1 mg/L (72 h)		Algae
propan-2-ol CAS: 67-63-0	LC50 9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50 10000 mg/L (24 h)	Daphnia magna	Crustacean
	EC50 Non-applicable		

#### Chronic toxicity:

Identification	Concentration	Species	Genus
2-aminoethanol CAS: 141-43-5	NOEC 1.24 mg/L	Oryzias latipes	Fish
	NOEC 0.85 mg/L	Daphnia magna	Crustacean
N,N-dimethyl dec-9-enamide CAS: 1356964-77-6	NOEC 0.71 mg/L	Danio rerio	Fish
	NOEC 1 mg/L	Daphnia magna	Crustacean

### 12.2 Persistence and degradability:

#### Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5	Non-applicable	Concentration	20 mg/L
2-aminoethanol CAS: 141-43-5	COD	Non-applicable	Period	21 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
N,N-dimethyl dec-9-enamide CAS: 1356964-77-6	BOD5	Non-applicable	Concentration	10 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	64 %

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
propan-2-ol CAS: 67-63-0	BOD5	1.19 g O <sub>2</sub> /g	Concentration	100 mg/L
	COD	2.23 g O <sub>2</sub> /g	Period	14 days
	BOD5/COD	0.53	% Biodegradable	86 %

### 12.3 Bioaccumulative potential:

#### Substance-specific information:

Identification	Bioaccumulation potential	
2-aminoethanol CAS: 141-43-5	BCF	3
	Pow Log	-1.31
	Potential	Low
propan-2-ol CAS: 67-63-0	BCF	3
	Pow Log	0.05
	Potential	Low

### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-aminoethanol CAS: 141-43-5	Koc	0.27	Henry	3.7E-5 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Non-applicable
	Surface tension	5.025E-2 N/m (77 °F)	Moist soil	Non-applicable
Decanoic acid CAS: 334-48-5	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1.313E-2 N/m (456.31 °F)	Moist soil	Non-applicable
Dibenzyl ether CAS: 103-50-4	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3.977E-2 N/m (77 °F)	Moist soil	Non-applicable
propan-2-ol CAS: 67-63-0	Koc	1.5	Henry	8.207E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.24E-2 N/m (77 °F)	Moist soil	Yes

### 12.5 Results of PBT and vPvB assessment:

Non-applicable

### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Disposal methods:

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Corrosivity. The next EPA hazardous waste number could apply: D002.

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

#### Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

#### Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

## SECTION 14: TRANSPORT INFORMATION

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 14: TRANSPORT INFORMATION (continued)

### Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



**14.1 UN number:** UN1760  
**14.2 UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (2-aminoethanol; sodium hydroxide)  
**14.3 Transport hazard class(es):** 8  
 Labels: 8  
**14.4 Packing group, if applicable:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

### Transport of dangerous goods by sea:

With regard to IMDG 42-24:



**14.1 UN number:** UN1760  
**14.2 UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (2-aminoethanol; sodium hydroxide)  
**14.3 Transport hazard class(es):** 8  
 Labels: 8  
**14.4 Packing group, if applicable:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Special regulations: 274, 223  
 EmS Codes: F-A, S-B  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
 Segregation group: Non-applicable  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



**14.1 UN number:** UN1760  
**14.2 UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (2-aminoethanol; sodium hydroxide)  
**14.3 Transport hazard class(es):** 8  
 Labels: 8  
**14.4 Packing group, if applicable:** III  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations specific for the product in question:

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

## SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; sodium hydroxide (1310-73-2) ; propan-2-ol (67-63-0)*
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: *2,2'-iminodiethanol (111-42-2)*
- CANADA-Domestic Substances List (DSL): *Water (7732-18-5) ; 2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; Dibenzyl ether (103-50-4) ; benzaldehyde (100-52-7) ; potassium octanoate (764-71-6) ; Decanoic acid (334-48-5) ; sodium hydroxide (1310-73-2) ; Sodium glycolate (2836-32-0) ; trisodium nitrilotriacetate (5064-31-3) ; Sodium octane-1-sulphonate monohydrate (5324-84-5) ; propan-2-ol (67-63-0) ; Sodium sulphate (7757-82-6) ; N,N-dimethyl dec-9-enamide (1356964-77-6) ; Fatty acids, coco, potassium salts (61789-30-8) ; Alcohol ethoxylated (C9-C11) (68439-46-3) ; Citric Acid (77-92-9) ; Dodecylbenzenesulphonic acid, compound with 2-aminoethanol (1:1) (26836-07-7)*
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: *2,2'-iminodiethanol (111-42-2) - 100 lb ; sodium hydroxide (1310-73-2) - 1000 lb*
- Hazardous Air Pollutants (Clean Air Act): *2,2'-iminodiethanol (111-42-2)*
- Massachusetts RTK - Substance List: *2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; benzaldehyde (100-52-7) ; sodium hydroxide (1310-73-2) ; trisodium nitrilotriacetate (5064-31-3) ; propan-2-ol (67-63-0) ; Sodium sulphate (7757-82-6)*
- Minnesota - Hazardous substances ERTK: *2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; benzaldehyde (100-52-7) ; sodium hydroxide (1310-73-2) ; propan-2-ol (67-63-0)*
- New Jersey Worker and Community Right-to-Know Act: *2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; benzaldehyde (100-52-7) ; sodium hydroxide (1310-73-2) ; propan-2-ol (67-63-0)*
- New York RTK - Substance list: *2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; benzaldehyde (100-52-7) ; sodium hydroxide (1310-73-2) ; propan-2-ol (67-63-0)*
- NTP (National Toxicology Program): Non-applicable
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: *2-aminoethanol (141-43-5) ; benzaldehyde (100-52-7)*
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; benzaldehyde (100-52-7) ; sodium hydroxide (1310-73-2) ; Sodium glycolate (2836-32-0) ; propan-2-ol (67-63-0) ; Sodium sulphate (7757-82-6)*
- Rhode Island - Hazardous substances RTK: *2,2'-iminodiethanol (111-42-2) ; sodium hydroxide (1310-73-2)*
- SB-258 Cleaning Product Right to Know Act: *2,2'-iminodiethanol (111-42-2) ; benzaldehyde (100-52-7) ; sodium hydroxide (1310-73-2) ; propan-2-ol (67-63-0) ; Sodium sulphate (7757-82-6)*
- The Toxic Substances Control Act (TSCA) : *Water (7732-18-5) ; 2-aminoethanol (141-43-5) ; 2,2'-iminodiethanol (111-42-2) ; Dibenzyl ether (103-50-4) ; benzaldehyde (100-52-7) ; potassium octanoate (764-71-6) ; Decanoic acid (334-48-5) ; sodium hydroxide (1310-73-2) ; Sodium glycolate (2836-32-0) ; trisodium nitrilotriacetate (5064-31-3) ; Sodium octane-1-sulphonate monohydrate (5324-84-5) ; propan-2-ol (67-63-0) ; Sodium sulphate (7757-82-6) ; N,N-dimethyl dec-9-enamide (1356964-77-6) ; Fatty acids, coco, potassium salts (61789-30-8) ; Alcohol ethoxylated (C9-C11) (68439-46-3) ; Citric Acid (77-92-9) ; Dodecylbenzenesulphonic acid, compound with 2-aminoethanol (1:1) (26836-07-7)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): *2,2'-iminodiethanol (111-42-2) ; trisodium nitrilotriacetate (5064-31-3) ; propan-2-ol (67-63-0)*

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

### Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

### Other information:

All ingredients in the product formula are listed on the TSCA Inventory.

## SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

### Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

### Texts of the legislative phrases mentioned in section 3:

- CONTINUED ON NEXT PAGE -



Printing: 12/3/2025

Date of compilation: 7/1/2025

Revised: 7/21/2025

Version: 4 (Replaced 3)

**SECTION 16: OTHER INFORMATION (continued)**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**29 CFR 1910.1200:**

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2A: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 4: H227 - Combustible liquid.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Advice related to training:**

According to 29 CFR 1910.1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

**Principal bibliographical sources:**

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

**NFPA:**

Health Hazards: 3

Flammability Hazards: 1

Instability Hazards: 0

Special Hazards: Non-applicable



Date of compilation: 7/1/2025

Revised: 7/21/2025

Information in this Safety Data Sheet (SDS) is based on sources other than direct test data and is given in good faith. No warranty is expressed or implied. We believe that the information is current as of the date of this SDS. The use of this information, the conditions, the methods of handling, storage, use and disposal of the product are not within the control of the manufacturer and distributor, therefore it is the user's responsibility and obligation to determine the conditions of the safe use of this product and to ensure that its activities comply with all laws and regulations.

**END OF SAFETY DATA SHEET**