DAYCON

Safety data sheet according to 29 CFR 1910.1200

- INDUSTRIAL PLUS



Page 1/13

SECTION 1: IDENTIFICATION

1.1 Product identifier: SDS033 - INDUSTRIAL PLUS

SDS033

Other means of identification:

ITEM CODE (GAL.): 202564

ITEM CODE (55 GAL.): INDPL55GAL

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses (Professional users):

- Cleaner

Relevant uses (Industrial user):

- Cleaner

For Professional users/Industrial user only.

RELEVANT USE (Industrial, Professional):

Degreaser

Concrete and Stone Cleaner

Detergent for use in Pressure Washers

Deck and Patio Cleaner

Vinyl Cleaner

Uses advised against:

- All uses not specified in this section or in section 7.3

1.3 Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party:

Daycon Products Company, Inc.

16001 Trade Zone Avenue

20774 Upper Marlboro - Maryland - United States

Phone: 800-394-0019 cswensen@daycon.com www.daycon.com

1.4 Emergency phone number: 800-535-5053

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

29 CFR 1910.1200:

Classification of the chemical in accordance with paragraph (d)(1)(i) of §1910.1200

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1A: Skin corrosion, Category 1A, H314

2.2 Label elements:

29 CFR 1910.1200:

Danger



Hazard statements:

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.

Precautionary statements:

P260: Do not breathe vapours

P264: Wash thoroughly after use.

P280: Wear protective gloves/protective clothing/eye protection/protective footwear.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a poison center/doctor.

Substances that contribute to the classification

Disodium metasilicate; tetrasodium ethylene diamine tetraacetate; sodium hydroxide

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1

DAYCON Landers in Facility Maintenance Solution

Safety data sheet according to 29 CFR 1910.1200

- INDUSTRIAL PLUS



SECTION 2: HAZARD(S) IDENTIFICATION (continued)

Additional labeling:

Keep out of the reach of children

2.3 Hazards not otherwise classified (HNOC):

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Aqueous solution based on surfactants, perfume and colourant.

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 7732-18-5	Water	75 - <100 %
CAS: 68991-48-0	Alcohols, C7-21, ethoxylated	2.5 - <10 %
CAS: 6834-92-0	Disodium metasilicate	2.5 - <10 %
	Eye Dam. 1: H318; Met. Corr. 1: H290; Skin Corr. 1B: H314; STOT SE 3: H335 - Danger	2.5 - < 10 %
CAS: 64-02-8	tetrasodium ethylene diamine tetraacetate	1 - <2.5 %
	Acute Tox. 4: H302; Eye Dam. 1: H318 - Danger	1 - <2.5 %
CAS: 497-19-8	sodium carbonate	1 - <2.5 %
CAS: 497-19-8	Eye Irrit. 2A: H319 - Warning	1 - \2.5 %
CAC: 1210 72 2	sodium hydroxide	<1 %
CAS: 1310-73-2	Skin Corr. 1A: H314 - Danger	<1 %
CAS: Non-	Quaternary ammonium compound	<1 %
applicable	Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger	<1 %
CAS: 2836-32-0	Sodium glycollate	<1 %
CAS: Non- applicable	Fragrance	<1 %
CAS: 4403-90-1	C.I.Acid Green 25	<1 %
CAS: 6359-98-4	C.I.Acid yellow 17	<1 %
CAS: 518-47-8	C.I.Acid Yellow 73	<1 %
CAS: 1330-38-7	C.I.Direct Blue 86	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation,however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 **Page 2/13**

DAYCON

Safety data sheet according to 29 CFR 1910.1200

- INDUSTRIAL PLUS



SECTION 4: FIRST-AID MEASURES (continued)

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and its inhalation, to the respiratory system. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

SDS033

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 **Page 3/13**

DAYCON Leaders in Facility Maintenance Solution

Safety data sheet according to 29 CFR 1910.1200

- INDUSTRIAL PLUS



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

For accidental releases in excess of reportables quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 41 °F

Maximum Temp.: 86 °F

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits	
sodium hydroxide	8-hour TWA PEL	2 mg/m ³
	Ceiling Values - TWA PEL	

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 **Page 4/13**

DAYCON Laaders in Facility Maintenance Solution

Safety data sheet according to 29 CFR 1910.1200

according to 25 Cr R 1510.1200

- INDUSTRIAL PLUS



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

SDS033

CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:

Identification	on Occupational exposure limits		
sodium hydroxide	PEL		2 mg/m ³
CAS: 1310-73-2	STEL		

NIOSH: Immediately Dangerous To Life or Health (IDLH) Values:

Identification	on Occupational exposure limits		
sodium hydroxide	TWA		
CAS: 1310-73-2	IDLH Value		10 mg/m ³

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

If the working conditions and/or safety measures adopted do not allow keeping the airborne concentration of the product below the exposure limits (if any) or at acceptable levels (if no exposure limits exist), suitable respiratory protection equipment chosen by a qualified professional should be used.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.11 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

E.- Bodily protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration.
	Anti-slip work shoes	Replace before any evidence of deterioration.

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 **Page 5/13**



- INDUSTRIAL PLUS



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

40 CFR Part 59 (VOC):

V.O.C.(weight-percent): 0 % weight V.O.C. at 68 °F: $0 \text{ kg/m}^3 (0 \text{ g/L})$

California Air Resources Board (CARB) - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight V.O.C. at 68 °F: $0 \text{ kg/m}^3 (0 \text{ g/L})$

South Coast Air Quality Management District (AQMD) - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight V.O.C. at 68 °F: $0 \text{ kg/m}^3 (0 \text{ g/L})$

Ozone Transport Commission (OTC) Rules - VOC Regulatory:

V.O.C.(weight-percent): 0 % weight V.O.C. at 68 °F: $0 \text{ kg/m}^3 (0 \text{ g/L})$

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F: Liquid Appearance: **Transparent** Color: Green Odor: Pleasant

Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 212 °F Vapour pressure at 68 °F: 2350 Pa

Vapour pressure at 122 °F: 12381.01 Pa (12.38 kPa)

Evaporation rate at 68 °F: Non-applicable *

Product description:

Density at 68 °F: 1064.6 kg/m³ 1.065

Relative density at 68 °F:

Dynamic viscosity at 68 °F: Non-applicable * Kinematic viscosity at 68 °F: Non-applicable * Kinematic viscosity at 104 °F: Non-applicable * Concentration: Non-applicable *

pH: 12 - 14

Vapour density at 68 °F: Non-applicable * Partition coefficient n-octanol/water 68 °F: Non-applicable *

*Non-applicable due to the nature of the product, not providing information property of its hazards.

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 Page 6/13

Safety data sheet

according to 29 CFR 1910.1200

- INDUSTRIAL PLUS

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility in water at 68 °F: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: Non Flammable (>199.4 °F)

Flammability (solid, gas): Non-applicable * Non-applicable * Autoignition temperature: Lower flammability limit: Non-applicable * Upper flammability limit: Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable * Non-applicable * Oxidising properties: Corrosive to metals: Non-applicable * Heat of combustion: Non-applicable * Aerosols-total percentage (by mass) of flammable Non-applicable *

components:

Other safety characteristics:

Surface tension at 68 °F: Non-applicable * Refraction index: Non-applicable *

*Non-applicable due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Not applicable

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 Page 7/13

DAYCON

Safety data sheet according to 29 CFR 1910.1200

- INDUSTRIAL PLUS



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

 IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
sodium carbonate	LD50 oral	2800 mg/kg	Rat
CAS: 497-19-8	LD50 dermal		
	LC50 inhalation		
	LC50 inhalation dust		



- INDUSTRIAL PLUS



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification Acute toxicity		toxicity	Genus
tetrasodium ethylene diamine tetraacetate	LD50 oral	1700 mg/kg	Rat
CAS: 64-02-8	LD50 dermal		
	LC50 inhalation		
	LC50 inhalation dust		
Sodium glycollate	LD50 oral	7110 mg/kg	Rat
CAS: 2836-32-0	LD50 dermal		
	LC50 inhalation		
	LC50 inhalation vapour		
C.I.Acid Green 25	LD50 oral	6700 mg/kg	Rat
CAS: 4403-90-1	LD50 dermal		
	LC50 inhalation		
	LC50 inhalation dust		
C.I.Acid Yellow 73	LD50 oral	>5000 mg/kg	Rat
CAS: 518-47-8	LD50 dermal		
	LC50 inhalation		
	LC50 inhalation dust		

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification		Concentration	Species	Genus
Disodium metasilicate	LC50	210 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 6834-92-0	EC50	216 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
tetrasodium ethylene diamine tetraacetate	LC50	121 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 64-02-8	EC50	140 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
sodium carbonate	LC50	740 mg/L (96 h)	Gambussia afinis	Fish
CAS: 497-19-8	EC50	265 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
sodium hydroxide	LC50	189 mg/L (48 h)	Leuciscus idus	Fish
CAS: 1310-73-2	EC50	33 mg/L	Crangon crangon	Crustacean
	EC50	Non-applicable		
Quaternary ammonium compound	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: Non-applicable	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
C.I.Acid Yellow 73	LC50	1372 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 518-47-8	EC50	337 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50	Non-applicable		

Chronic toxicity:

Identification	Concentration		Species	Genus
tetrasodium ethylene diamine tetraacetate	NOEC	25.7 mg/L	Danio rerio	Fish
CAS: 64-02-8	NOEC	25 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Non-applicable

12.3 Bioaccumulative potential:

Substance-specific information:

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 **Page 9/13**

Safety data sheet

according to 29 CFR 1910.1200

- INDUSTRIAL PLUS



SECTION 12: ECOLOGICAL INFORMATION (continued)

SDS033

Identification	Bioaccumulation potential	
tetrasodium ethylene diamine tetraacetate	BCF	2
CAS: 64-02-8	Pow Log	-13
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
tetrasodium ethylene diamine tetraacetate	Koc	1046	Henry	0E+0 Pa·m³/mol
CAS: 64-02-8	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Corrosivity. The next EPA hazardous waste number could apply: D002.

IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO EVALUATE WHETHER HIS WASTES ARE HAZARDOUS BY CHARACTERISTICS OR LISTING.

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



14.1 UN number: UN3267

14.2 UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Disodium

metasilicate)

14.3 Transport hazard class(es): Labels: 8 14.4 Packing group, if applicable: $\, {\rm II} \,$ 14.5 Marine pollutant: No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9 Limited quantities: 1 I

14.7 Transport in bulk (according Non-applicable

to Annex II of MARPOL 73/78 and the IBC Code):

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 Page 10/13



SDS033

- INDUSTRIAL PLUS



Page 11/13

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: UN3267

14.2 UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Disodium

metasilicate)

14.3 Transport hazard class(es): 8

abels: 8

14.4 Packing group, if applicable: II **14.5 Marine pollutant:** No

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Special regulations: 274

EmS Codes: F-A, S-B

Physico-Chemical properties: see section 9

Limited quantities: 1 L Segregation group: SGG18

14.7 Transport in bulk (according Non-applicable

to Annex II of MARPOL 73/78 and the IBC Code):

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:



14.1 UN number: UN3267

14.2 UN proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Disodium

metasilicate)

14.3 Transport hazard class(es): 8 Labels: 8

14.4 Packing group, if applicable: II **14.5** Marine pollutant:

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

14.7 Transport in bulk (according Non-applicable

to Annex II of MARPOL 73/78 and the IBC Code):

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1



DS033

- INDUSTRIAL PLUS



SECTION 15: REGULATORY INFORMATION (continued)

- CALIFORNIA LABOR CODE The Hazardous Substances List: sodium hydroxide (1310-73-2)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Birth defects or other reproductive harm: Non-applicable
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) Cancer: Non-applicable
- CANADA-Domestic Substances List (DSL): Water (7732-18-5); Alcohols, C7-21, ethoxylated (68991-48-0); Disodium metasilicate (6834-92-0); tetrasodium ethylene diamine tetraacetate (64-02-8); sodium carbonate (497-19-8); sodium hydroxide (1310-73-2); Sodium glycollate (2836-32-0); C.I.Acid Green 25 (4403-90-1); C.I.Acid yellow 17 (6359-98-4); C.I.Acid Yellow 73 (518-47-8); C.I.Direct Blue 86 (1330-38-7)
- CANADA-Non-Domestic Substances List (NDSL): Non-applicable
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Reportable Quantities: sodium hydroxide (1310-73-2) 1000 lb
- Hazardous Air Pollutants (Clean Air Act): Non-applicable
- Massachusetts RTK Substance List: sodium hydroxide (1310-73-2)
- Minnesota Hazardous substances ERTK: sodium hydroxide (1310-73-2)
- New Jersey Worker and Community Right-to-Know Act: sodium hydroxide (1310-73-2)
- New York RTK Substance list: sodium hydroxide (1310-73-2)
- NTP (National Toxicology Program): Non-applicable
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
- Pennsylvania Worker and Community Right-to-Know Law: Non-applicable
- Protective Action Criteria (PAC) with AEGLs, ERPGs, & TEELs: *Alcohols, C7-21, ethoxylated (68991-48-0)*; *Disodium metasilicate (6834-92-0)*; *tetrasodium ethylene diamine tetraacetate (64-02-8)*; *sodium carbonate (497-19-8)*; *sodium hydroxide (1310-73-2)*; *Sodium glycollate (2836-32-0)*
- Rhode Island Hazardous substances RTK: sodium hydroxide (1310-73-2)
- SB-258 Cleaning Product Right to Know Act: sodium hydroxide (1310-73-2)
- The Toxic Substances Control Act (TSCA): Water (7732-18-5); Alcohols, C7-21, ethoxylated (68991-48-0); Disodium metasilicate (6834-92-0); tetrasodium ethylene diamine tetraacetate (64-02-8); sodium carbonate (497-19-8); sodium hydroxide (1310-73-2); Sodium glycollate (2836-32-0); C.I.Acid Green 25 (4403-90-1); C.I.Acid yellow 17 (6359-98-4); C.I.Acid Yellow 73 (518-47-8); C.I.Direct Blue 86 (1330-38-7)
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H318: Causes serious eye damage.

H314: Causes severe skin burns and eye damage.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:

Acute Tox. 4: H302 - Harmful if swallowed.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2A: H319 - Causes serious eye irritation.

Met. Corr. 1: H290 - May be corrosive to metals.

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

According to 29 CFR 1910. 1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).



- INDUSTRIAL PLUS



SECTION 16: OTHER INFORMATION (continued)

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon IARC: International Agency for Research on Cancer

Date of compilation: 5/5/2025

Information in this Safety Data Sheet (SDS) is based on sources other than direct test data and is given in good faith. No warranty is expressed or implied. We believe that the information is current as of the date of this SDS. The use of this information, the conditions, the methods of handling, storage, use and disposal of the product are not within the control of the manufacturer and distributor, therefore it is the user's responsibility and obligation to determine the conditions of the safe use of this product and to ensure that its activities comply with all laws and regulations.

END OF SAFETY DATA SHEET

Printing: 5/13/2025 Date of compilation: 5/5/2025 Version: 1 **Page 13/13**