

Daycon Products Company, Inc.  
16001 Trade Zone Avenue, Upper Marlboro, MD 20774  
Local: (301) 218-1000  
Toll Free: (800) 394-0019  
Fax: (301) 218-7191

# DEEP LUSTRE

## *High Solids Floor Seal and Finish*

### Specifications:

Appearance: Opaque liquid  
Color: White  
Odor: Mild acrylic  
Total Solids: 25%  
Use Dilution: As is  
Coverage (First coat): 1200-1800 sq. ft./gal.  
Coverage (Recoating): 1500-2000 sq. ft./gal.  
Storage Stability: Two years  
minimum in sealed  
container  
Protective Clothing: See Safety Data  
Sheet (SDS)  
Coverage: 1500 - 2000 sq. ft. per  
gallon  
VOC's, % as is: Less than 10  
Product Conformance: Manufactured by an  
ISO 9001:2015 registered company.

### Comment:

Daycon Deep Lustre meets or exceeds C.S.M.A. and U.L. slip resistance standards: of 0.5 minimum as tested by an outside laboratory in accordance with A.S.T.M. -D-2047-82 by a James machine. To maintain high gloss, only neutral cleaners such as Daycon Kleer N' Brite, KBQ-256, KBQ-32, Spectra 4, Spectra 25, Spectra 305, or Spectra 405 should be used in damp mopping or scrubbing. Daycon Maintainer Plus, Sunrise, or Burnishing Gel #27 should be used when burnishing the floor.

### Packaging:

Five Gallon Pail  
Item Code: DL255GAL  
Gallon (4 per case)  
Item Code: 336689  
55 Gallon Drum  
Item Code: DL2555GAL

### Date:

February 7, 2018

### Description:

Deep Lustre is a high solids, extended wear, scratch and scuff resistant, non-yellowing pure acrylic floor seal and finish. It contains a state-of-the-art highly cross linked polymer that makes it extremely durable, scrubbable, and maintainable with low or ultra high speed floor machines. Because of its high solids, it requires fewer coats, has a high initial shine, and can be easily restored.

### Benefits:

- Requires less maintenance than conventional floor finishes
- 25% solids formula requires less coats
- Acrylic polymer resists yellowing with age
- High clarity brings out true color and gloss of floor
- Dries in 20 to 30 minutes
- Easily removed with Daycon Renegade, Meteor, Hurricane, or G-Force

### Product Disposal:

This product is non-hazardous material. Dispose of in accordance with local, state, and federal regulations. It is recommended that the high density polyethylene container and any corrugated packaging be recycled.

### Directions:

1) Prepare the floor, first, by stripping and neutralizing the surface. 2) For best results, use a white, nylon, finishing mop to apply product. Apply one coat of Deep Lustre 25, allowing 20-30 minutes drying time between coats. **DO NOT RECOAT UNTIL THE PREVIOUS COAT IS COMPLETELY DRY.** Buff or burnish to produce a beautiful finish. 3) Maintain with high speed burnishing or low speed buffing. Can dry burnish or use Daycon's Maintainer Plus, Sunrise, Express, or Burnishing Gel #27. To maintain high gloss, only neutral cleaners such as Daycon Kleer N' Brite, KBQ-256, KBQ-32, Spectra 4, Spectra 25, Spectra 305, or Spectra 405 should be used in damp mopping or scrubbing.