



## Product Information Sheet

Daycon Products Company, Inc. 16001 Trade Zone Avenue, Upper Marlboro, MD 20774  
Local: (301) 218-1000 Toll Free: (800) 394-0019 Fax (301) 218-7191

This sheet is not a Material Safety Data Sheet (M.S.D.S.), nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described herein is for use only by trained, professional, cleaning personnel.

# EZ-33

## High Solids Floor Finish

### Description:

EZ-33 is a 33%, high-solids, floor finish that can be applied with a conventional finish mop. It has excellent durability, leveling, and gloss capabilities. Three coats of EZ-33 is equivalent to five or six coats of conventional finishes, saving 35% to 50% of the finishing labor at no increase in product cost. EZ-33 responds to both propane and UHS electric burnishing. It can be dry burnished or rejuvenated with Daycon Maintainer Plus. EZ-33 dries in 30-40 minutes under normal conditions.

### Benefits:

- Labor savings
- Dazzling gloss
- Applies like standard floor finish
- High-speed formulation

### Specifications:

|                        |  |
|------------------------|--|
| Appearance:            | Opaque Liquid  |
| Color:                 | White  |
| Odor:                  | Mild Acrylic   |
| Total Solids:          | 33% ± 0.4%   |
| Use dilution:          | As is  |
| Coverage (First coat): | 1200-1500 sq. ft./gal.                               |
| Coverage (Recoating):  | 1500-2000 sq. ft./gal.                               |
| Storage Stability:     | Two years minimum in a sealed container              |
| Protective Clothing:   | See Safety Data Sheet (SDS)                          |
| VOC's, % as is:        | 0.0 lbs. /gal.                                       |
| Product Conformance:   | Manufactured by an ISO 9001:2008 registered company. |

### Comments:

EZ-33 can be applied over an existing finish that has been deep scrubbed with Daycon Kleer 'N Brite and a blue cleaning pad. For best results, a nylon finishing mop head (A03613) should be used, and burnishing with a beige pad between the second and third coat is suggested. During maintenance, a natural hair pad may be used to remove scratches, and a beige pad may be used to give the best gloss.

### Directions:

1) Prepare the floor, first, by stripping and neutralizing the surface. 2) For best results, use a white, nylon, finishing mop to apply product. Apply two coats of EZ-33, allowing 30-40 minutes drying time between coats. DO NOT RECOAT UNTIL THE PREVIOUS COAT IS COMPLETELY DRY. Prior to laying down the third coat, burnish with a beige pad, then recoat. 3) Maintain EZ-33 with high speed burnishing using a beige pad. Can dry burnish or use Daycon's Maintainer Plus, Sunrise, Express, or Burnishing Gel #27.

### Product Disposal:

This product is non-hazardous material. Dispose of in accordance with local, state, and federal regulations. It is recommended that the high density polyethylene container and any corrugated packaging be recycled.

**Packed:**

| <b>Packaging/Description</b> | <b>Item Code</b> |
|------------------------------|------------------|
| Gallon (4 per case)          | 502500           |
| 5 Gallon Pail                | EZ335GAL         |
|                              |                  |

**Date:**

April 10, 2013