



Product Information Sheet

Daycon Products Company, Inc. 16001 Trade Zone Avenue, Upper Marlboro, MD 20774
Local: (301) 218-1000 Toll Free: (800) 394-0019 Fax (301) 218-7191

This sheet is not a Material Safety Data Sheet (M.S.D.S.), nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described herein is for use only by trained, professional, cleaning personnel.

FLEXCOAT

Urethane-Acrylic Floor Finish

Description:

Flexcoat is a urethane-acrylic floor finish specifically formulated to finish rubberized floors and synthetic all-purpose sport floors. Flexcoat has excellent adhesion to all surfaces and has the flexibility needed to stand up to the wear created by multiple sporting events. Flexcoat exhibits outstanding shine and durability and may be burnished up to speeds of 3,000 RPM.

Flexcoat may also be used on Permagrain flooring, and Pirelli or rubberized tile by mixing one part Flexcoat with three parts water and then applying it to the surface with a Fast Finish Mop. Once dry, the floor may be burnished.

Benefits:

- For rubberized and synthetic sport floors
- Resists traffic and wear
- Excellent adhesion to all surfaces
- Tough and flexible
- Will not discolor
- May be used with Ultra-High Speed
- May be used on Permagrain flooring
- May be used on Pirelli tile

Specifications:

Appearance:	Opaque liquid
Color:	White
Odor:	Ammoniacal
Specific Gravity:	1.03 +/- .005
Total solids:	20% min.
VOCs:	3.9 % w+/- .1%
PH: As Is:	8.0-9.1
Flash point:	None
Use dilution:	As is for all purpose. Synthetic sport floors; 3 parts water to 1 part Flexcoat for Permagrain and Pirelli Tile.
Storage stability:	Two year minimum in a sealed container.
Protective clothing:	Rubber Gloves

Upc-A-Code:

1 gallon 704474017907

Interleaved 2 of 5: 50704474017902

Code:

662776

Date: December 29, 2011