



Product Information Sheet

Daycon Products Company, Inc. 16001 Trade Zone Avenue, Upper Marlboro, MD 20774
Local: (301) 218-1000 Toll Free: (800) 394-0019 Fax (301) 218-7191

This sheet is not a Safety Data Sheet (S.D.S.), nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described herein is for use only by trained, professional, cleaning personnel.

HURRICANE

Floor Wax & Finish Remover

Description:

Hurricane is a high efficiency stripper for heavy build-ups. Its low alkalinity makes it the ideal stripper for marble, terrazzo, slate, granite, quarry tile, and brick, as well as conventional tile floors. Its low foaming properties make it an excellent choice for use in automatic scrubbers. Hurricane contains no ammonia or caustics.

Benefits:

- Low alkali content makes rinsing easier; leaves no white residue
- Removes ultra high speed and urethane based finishes
- Excellent grout and mortar cleaning ability
- Safe on stone and brick floors
- Works in hot or cold water

Specifications:

Appearance:	Clear Liquid
Color:	Red
Odor:	Strong 2-butoxyethanol (Ethylene glycol butyl ether)
Use Dilution:	1:8 to 1:5.3 (16 oz. - 24 oz. per gallon)
Storage Stability:	Minimum two years in sealed container
Protective Clothing:	See Safety Data Sheet (SDS)
VOC Content: (as is):	28% by weight
Product Conformance:	Manufactured by an ISO 9001:2008 registered company

Comments:

This product is not designed for use on asphalt tile, linoleum, or rubber floors. Do not use without first testing in a small area. Avoid skin and eye contact. Remove any contaminated clothing. Do not use in unventilated areas. Always wash hands or other exposed skin immediately and before eating, drinking or smoking. Use one ounce per gallon of Daycon Ready Neutralizer in final rinse to ensure the floor is satisfactory for sealing and finishing. Coverage, sq. ft./gal. Hurricane is approximately 200-500 sq. ft. per gallon of mixed product.

Directions:

Machine Stripping: 1) Mix 8 oz. - 16 oz. Hurricane with 1 gallon of water. 2) Apply to floor using tank feed system on machine. 3) Allow 5 to 10 minutes for solution to work, then agitate with machine. Since heavy build-up clogs pads quickly, they should be changed and rinsed often. **Mop-on/Mop-off Stripping:** 1) Mix 24 oz. - 32 oz. Hurricane with 1 gallon of water. 2) Apply to floor with mop and bucket. Agitate solution for 10 minutes following application. 3) Pick up dirty solution and mop floor with clean water. 4) For optimum results, it is recommended to use Daycon Kleer 'N Brite at 1 oz./gal of water in the final rinse.

Product Disposal:

This is a hazardous material. Dispose of in approved landfill in accordance with local, state, and federal regulations.

Packed:

Packaging/Description	Item Code
Gallon (4 per case)	217900
5 Gallon Pail	HURR5GAL
55 Gallon Drum	HURR55GAL

Date:

April 10, 2013