



Product Information Sheet

Daycon Products Company, Inc. 16001 Trade Zone Avenue, Upper Marlboro, MD 20774
Local: (301) 218-1000 Toll Free: (800) 394-0019 Fax (301) 218-7191

This sheet is not a Safety Data Sheet (SDS), nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described herein is for use only by trained, professional, cleaning personnel.

KNOCK-OUT Oven and Grill Cleaner

Description: Knock-Out oven and grill cleaner is a time proven, fast-acting, heavy-duty formula that removes grease, carbon, and baked-on food residue from the dirtiest stove, oven, fryer, grill, iron and stainless cookware. Knockout contains no harmful solvents or ammonia. Knockout requires no heat to work, and rinses easily and completely.

- Benefits:**
- Begins to work instantly, no long waiting period
 - No noxious fumes or vapors
 - Removes the toughest baked on residues
 - Works without heating oven
 - Completely biodegradable

Specifications:

Appearance:	Clear liquid
Color:	Brown
Odor:	Mild glycol
Use Dilution:	As is for cleaning, 1:5 for parts soaking
Storage Stability:	Two years minimum in sealed containers
Protective Clothing:	See Safety Data Sheet (SDS)
VOC's, % as is:	0
Product Conformance:	Manufactured by an ISO 9001:2008 registered company.

Comments: Knock-Out should not be used on aluminum, copper, or brass surfaces. Discoloration, pitting, or destruction of the metal may occur. Knockout is corrosive to eyes and skin. Flush with water immediately if contact occurs.

Directions: **For Average Buildup:** 1) Spread cleaner evenly over surfaces using cloth, sponge or steel wool. 2) Let dwell for 10-60 minutes. 3) Wipe or scrape surface clean with damp cloth, sponge or steel wool. (Apply more cleaner to stubborn areas). 4) Thoroughly wipe surface to remove all residue. Then wipe surface dry. **For Extra Heavy Buildup:** 1) Rub heavy buildup areas moderately with steel wool or abrasive pad to "break" the top crust layer. This mild action will activate very rapid chemical activity on the deeper layers by Knock-Out. 2) Preheat the oven to about 140°F. This promotes more rapid, effective softening and removal. 3) Then apply Knock-Out to the surface. 4) Allow the cleaner to remain on surface overnight before final cleaning, only if necessary!

Product Disposal: Dispose of in accordance with local, state, and federal regulations. It is recommended that the high density polyethylene container and any corrugated packaging be recycled.

Packed:

Packaging/Description	Item Code
Gallon (4 per case)	338833
55 Gallon Drum (Special Order)	KNOCK55GAL

Date: May 3, 2013