

Daycon Products Co., Inc.  
16001 Trade Zone Ave.  
Upper Marlboro, MD 20774  
800.394.0019  
www.daycon.com

**GAL. ITEM NO: 208750**  
**64 OZ. ITEM NO: 564655**

# MAINTAINER PLUS

*Acrylic and Urethane Floor Finish Maintainer*

## Specifications:

Appearance:	Clear Liquid
Color:	Pink
Odor:	Peppermint
Use Dilution:	1:64 to 1:32 (2-4 oz./gal)
Coverage (sq.ft./gal):	Approx. 4,000 (mop on)
Storage Stability:	Two years in a sealed container
Protective Clothing:	Neoprene or nitrile gloves. Splash proof safety goggles with side shields
VOC's (% as is):	0.94
Conformance:	Manufactured by an ISO 9001:20015 registered company

## Comment:

Improper use dilution may result in damage to surfaces and may increase the risk of health effects. Daycon Maintainer Plus contains no waxes to soften the surface and cause potential slip problems.

## Packaging:

Gallon (4 per case)  
Item Code: 208750

64 OZ. Dual Chamber Bottle (6 per case)  
Item Code: 564655

## Date:

October 11, 2017

## Description:

Maintainer Plus is a high or low speed maintainer for acrylic and acrylic/urethane floor finishes. It is used as a mop on product. Maintainer Plus not only gives a high gloss and wet look, it is also an excellent cleaner. Maintainer Plus may be used in automatic scrubbers or may be used with a low or high speed machine when top scrubbing the floor. It is formulated to use at 2 - 4 ounces per gallon of water.



**Green Seal Certification Statement:** This product meets Green Seal™ Standard GS-53 based on effective performance, concentration of product, minimized/recycled packaging, and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

## Benefits:

- Increases slip resistance
- High dilution factor for economy use
- Restores gloss and appearance without finish buildup
- Does not soften finish surface
- Burnishes out quickly for productivity
- Excellent cleaner

## Product Disposal:

Dispose of in accordance with local, state, and federal regulations. It is recommended that the high density polyethylene container and any corrugated packaging be recycled.

## Directions:

Use Maintainer Plus with cold water from the tap at 1:64 to 1:32, or 2-4 ounces of product per gallon. Mop solution down and allow to dry. Alternatively, Maintainer Plus may be applied with an automatic scrubber. Once the floor is dry, burnish the floor with a natural hair or beige pad. If a burnisher is unavailable, buff the floor with a low speed machine. In all cases, the floor must be burnished after applying Maintainer Plus.

## Ingredients:

Water, Cross-linked polyethylene glycol, Nonionic Surfactant Blend, C9-11 Parath-6, PEG-180, Glycolic Acid, Methylisothiazolinone, Fragrance, Fluorosurfactant, CI 45220, CI 45100. Fragrance is listed on IFRA list of fragrance materials, which can be found at [goo.gl/idXnTX](http://goo.gl/idXnTX)