



Product Information Sheet

Daycon Products Company, Inc. 16001 Trade Zone Avenue, Upper Marlboro, MD 20774
Local: (301) 218-1000 Toll Free: (800) 394-0019 Fax (301) 218-7191

This sheet is not a Safety Data Sheet (SDS), nor does it satisfy the requirements to have one. All information on this sheet is believed to be accurate, but no warranty is expressed or implied. The product described herein is for use only by trained, professional, cleaning personnel.

TOP GUN

High Solids Floor Finish

Description: Top Gun is an innovative, ultra-high durability, high-gloss floor finish and seal based on a fluorinated acrylic polymer. This chemistry makes it the toughest finish on the market; resisting wear and abrasion 50% longer than conventional acrylic finishes. It also has improved stain and soil resistance. These properties make it ideal for high traffic usage such as retail stores, schools, hospitals, lobbies, etc.

Top Gun can be dry burnished with either electric or propane machines with less dusting than conventional finishes. You can expect to put 40% less labor into maintaining the floor; less burnishing, less top scrubbing, less recoating, and less stripping while maintaining exceptional gloss and clarity.

Benefits:

- Excellent Initial Gloss
- Excellent Burnish Response
- Lasts 50% longer than conventional finishes
- Labor Savings
- Low VOCs

Specifications:

Appearance:	Opaque liquid
Color:	White
Odor:	Mild acrylic
Total Solids:	22% ± .5
Use dilution:	As is
Coverage (First coat):	1500-2000 sq. ft./gal.
Coverage (Recoating):	2000 sq. ft./gal.
Storage Stability:	Two years minimum in sealed container.
Protective Clothing:	See Safety Data Sheet (SDS)
VOC's, % as is:	2.61
Product Conformance:	Manufactured by an ISO 9001:2008 registered company.

Comments: Top Gun can be applied over most existing finishes once they are top scrubbed with a blue pad and neutral cleaner.

% Styrene (Free Monomer): 0.0

Directons: 1) Prepare the floor, first, by stripping and neutralizing the surface. Use Daycon G-Force, Renegade, Hurricane or LOS to strip, and Daycon Ready to neutralize the surface. 2) For best results, use a white, nylon, finishing mop to apply product. Apply a thin coat of Top Gun, allowing 20-30 minutes drying time, before adding second coat. DO NOT RECOAT UNTIL THE PREVIOUS COAT IS COMPLETELY DRY. Buffing will produce a beautiful finish. 3) Maintain Top Gun daily by dust mopping, damp mopping or scrubbing, then buffing once the surface is dry.

Product Disposal: This product is non-hazardous material. Dispose of in sewer or approved landfill in accordance with local, state, and federal regulations. It is recommended that the high density polyethylene container and any corrugated packaging be recycled.

Packed:

Packaging/Description	Item Code
Gallon (4 per case)	305768
5 Gallon Pail	TOPGUN5GAL
55 Gallon Drum	TOPGUN55GAL

Date: May 7, 2013