



Armstrong S-750 Premium Tile Adhesive

S-750

MSDS Preparation Date (mm/dd/yyyy): 06/22/2012

Page 1 of 6

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : **Armstrong S-750 Premium Tile Adhesive**

Product Code(s) : S-750

Product Use : Adhesive for installation of Vinyl Composition Tile (VCT).

Chemical Family : Mixture.

Supplier's name and address:

Manufacturer's name and address:

Armstrong World Industries, Inc.

Refer to Supplier

2500 Columbia Ave.
Lancaster, PA, U.S.A.
17603

Information Telephone # :

24 Hr. Emergency Tel # : CHEM-TEL: 1-800-255-3924 or 1-813-248-0585 (call collect)

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS classification:
This product is not a WHMIS controlled product in Canada. It does not meet any of the criteria for a controlled product provided in Part IV of the Controlled Products Regulations (CPR).

OSHA Classification: This product is considered to be a non-hazardous substance under OSHA standard 29 CFR 1910.1200.

Emergency Overview : Beige paste. Mild odour.
May cause respiratory irritation. May cause gastrointestinal irritation.
Possible transient eye irritation. May cause mild skin irritation.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause mild transient irritation. May cause coughing and breathing difficulties.

Skin : May cause mild skin irritation.

Eyes : May cause mild transient irritation. Symptoms may include stinging and tearing.

Ingestion : May cause irritation of mouth, throat, and stomach. May cause nausea, vomiting, and diarrhea.

Effects of long-term (chronic) exposure

: Prolonged skin contact may cause skin irritation.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt.%</u>
No hazardous ingredients	N/Ap	N/Ap

SECTION 4 - FIRST AID MEASURES



Armstrong S-750 Premium Tile Adhesive

S-750

MSDS Preparation Date (mm/dd/yyyy): 06/22/2012

Page 2 of 6

- Inhalation** : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. Obtain medical attention if symptoms develop and persist.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Wash affected areas with soap and water. If irritation or symptoms develop, seek medical attention. Wash contaminated clothing before re-use.
- Eye contact** : Immediately flush eye(s) with plenty of water. If irritation persists, seek prompt medical attention.
- Ingestion** : Do not induce vomiting. Consult a physician. Never give anything by mouth to an unconscious person.
- Notes For Physician** : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

- : Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.1200)

- : Combustible Liquid Class III B.

Oxidizing properties

- : None known.

Explosion data: Sensitivity to mechanical impact / static discharge

- : Not expected to be sensitive to mechanical impact or static discharge.

Suitable extinguishing media

- : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Do not use water jet, as this may spread burning material.

Special fire-fighting procedures/equipment

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

Hazardous combustion products

- : Carbon dioxide; Carbon monoxide; Acrylic monomer.; Nitrogen oxides

NFPA Rating

- | | | | | |
|------------------|------------------------|-----------------------|-------------------------|------------|
| 0 - Minimal | 1 - Slight | 2 - Moderate | 3 - Serious | 4 - Severe |
| <i>Health:</i> 1 | <i>Flammability:</i> 1 | <i>Instability:</i> 0 | <i>Special Hazards:</i> | None |

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions

- : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. For personal protection see section 8.

Environmental precautions

- : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Spill response/cleanup

- : Ventilate area of release. Remove all sources of ignition. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.

Prohibited materials

- : None known.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): None reportable.

SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures

- : Use in a well-ventilated area. Wear suitable protective equipment during handling. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and flame. Avoid contact with incompatible materials. Wash thoroughly after handling.



Armstrong S-750 Premium Tile Adhesive

S-750

MSDS Preparation Date (mm/dd/yyyy): 06/22/2012

Page 3 of 6

- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from direct sunlight. Keep away from incompatibles. Inspect periodically for damage or leaks.
- Incompatible materials** : Metal salts.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

<u>Exposure Limits</u>				
<u>Ingredients</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
No hazardous ingredients	N/Ap	N/Ap	N/Ap	N/Ap

Ventilation and engineering measures

- : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

- : None required under normal conditions. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised.

Skin protection

- : Gloves impervious to the material are recommended. Advice should be sought from glove suppliers.

Eye / face protection

- : Safety glasses with side-shields or chemical splash goggles.

Other protective equipment

- : Depending on conditions of use, an impervious apron should be worn. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

- : Avoid breathing vapors, fumes or dust. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Remove soiled clothing and wash it thoroughly before reuse. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|---|--|
| Physical state : paste | Appearance : beige |
| Odour : mild | Odour threshold : N/Av |
| pH : 9.0 - 10.0 | |
| Boiling point : 100°C (212°F) | Specific gravity : 1.135 |
| Melting/Freezing point : N/Av | Coefficient of water/oil distribution : N/Av |
| Vapour pressure (mmHg @ 20° C / 68° F) : N/Av | Solubility in water : Miscible |
| Vapour density (Air = 1) : N/Av | Evaporation rate (n-Butyl acetate = 1) : N/Av |
| Volatile organic Compounds (VOC's) : 5.9 g/L | Volatiles (% by weight) : 44-46% |
| Flash point : > 149°C (> 300°F) | |
| Flash point Method : Pensky Martens Closed Cup | Auto-ignition temperature : N/Av |
| Lower flammable limit (% by vol.) : N/Ap | Upper flammable limit (% by vol.) : N/Ap |
| Flame Projection Length : N/Ap | Flashback observed : N/Ap |
| Viscosity : 14,000 cSt | |
| Absolute pressure of container : N/Ap | |

Section 10: Stability And Reactivity

- Stability and reactivity** : Stable under the recommended storage and handling conditions prescribed.



Armstrong S-750 Premium Tile Adhesive

S-750

MSDS Preparation Date (mm/dd/yyyy): 06/22/2012

Page 4 of 6

- Hazardous polymerization** : Hazardous polymerisation does not occur.
- Conditions to avoid** : Avoid heat and open flame. Keep away from direct sunlight. Do not use in areas without adequate ventilation.
- Materials To Avoid And Incompatibility** : See Section 7 (Handling and Storage) for further details.
- Hazardous decomposition products** : Refer to Section 5 for additional 'Hazardous combustion products'.

SECTION 11 - TOXICOLOGICAL INFORMATION

- Target organs** : Eyes, skin, respiratory system and digestive system.
- Routes of exposure** : *Inhalation:* YES *Skin Absorption:* NO *Skin & Eyes:* YES *Ingestion:* YES
- Toxicological data** : There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	<u>LC₅₀(4hr)</u> <u>inh. rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
No hazardous ingredients	N/Ap	N/Ap	N/Ap

- Carcinogenic status** : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
- Reproductive effects** : None known.
- Teratogenicity** : Not expected to be a teratogen.
- Mutagenicity** : None known.
- Epidemiology** : Not known.
- Sensitization to material** : None known.
- Synergistic materials** : None known.
- Irritancy** : Mild.
- other important hazards** : None known.
- Conditions aggravated by overexposure** : Pre-existing skin, eye and respiratory disorders.

SECTION 12 - ECOLOGICAL INFORMATION

- Ecotoxicity** : No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
- Mobility** : No information available.
- Persistence** : No information available.
- Bioaccumulation potential** : No information available.
- Other Adverse Environmental effects** : No information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7.
- Methods of Disposal** : Dispose of in accordance with federal, provincial and local hazardous waste laws.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label



Armstrong S-750 Premium Tile Adhesive

S-750

MSDS Preparation Date (mm/dd/yyyy): 06/22/2012

Page 5 of 6

TDG	none	Not regulated.	Not regulated	none	
TDG Additional information	None.				
49CFR/DOT	None.	Not regulated.	Not regulated	none	
49CFR/DOT Additional information	None.				

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

TSCA information: All ingredients are listed on the TSCA inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: This product does not contain any substances with SARA reporting requirements.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

Other U.S. State "Right to Know" Lists: None known or reported by the manufacturer.

International Information:

Canadian Environmental Protection Act (CEPA): All components of this product are on the Canadian DSL list.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION

HMIS Rating : * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe
Health: 1 *Flammability:* 1 *Reactivity:* 0

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- CAS: Chemical Abstract Services
- CPR: Controlled Products Regulation
- DSL: Domestic Substances List
- IARC: International Agency for Research on Cancer
- Inh: Inhalation
- LC: Lethal Concentration
- LD: Lethal Dose
- N/Ap: Not Applicable
- N/Av: Not Available
- NIOSH: National Institute of Occupational Safety and Health
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PEL: Permissible exposure limit
- RTECS: Registry of Toxic Effects of Chemical Substances



Armstrong S-750 Premium Tile Adhesive

S-750



MSDS Preparation Date (mm/dd/yyyy): 06/22/2012

Page 6 of 6

STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
TSCA: Toxic Substance Control Act
WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2012.
- 2. International Agency for Research on Cancer Monographs, searched 2012.
- 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2012 (Chempendium and RTECs).
- 4. Material Safety Data Sheet from manufacturer.
- 5. US EPA Title III List of Lists, July 2011 version.
- 6. California Proposition 65 List - March 16, 2012 version.

<p>Prepared for: Armstrong World Industries, Inc. 2500 Columbia Ave. Lancaster, PA, U.S.A., 17603 Telephone: 877-276-7876 Please direct all enquiries to Armstrong World Industries.</p>	
<p>Prepared by: ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Armstrong World Industries, Inc. and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Armstrong World Industries, Inc. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Armstrong World Industries, Inc.

Preparation Date (mm/dd/yyyy)

: 06/22/2012

END OF DOCUMENT