

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677

CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **TAYLOR 2020 WOOD MASTER ENGINEERED FLOOR ADHESIVE**
ITEM NUMBER: 2020-4
ITEM DESCRIPTION: Taylor 2020 Wood Master Engineered Floor Adh 4-Gal
PRODUCT DESCRIPTION: MASTIC
CHEMICAL FAMILY: AMIDE-ESTER-ACRYLATE BLEND
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE: 01/23/14 PRINT TIME: 13:29

HMIS HAZARD RATING

LEAST: 0	HEALTH: 1
SLIGHT: 1	FLAMMABLE: 0
MODERATE: 2	REACTIVITY: 0
HIGH: 3	
EXTREME: 4	

PREPARED BY: ROBERT DDAMULIRA
PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

No Hazardous ingredients per current OSHA regulations.

SECTION III PHYSICAL DATA

<u>Hazard</u>	<u>CAS #</u>	<u>WT/Wt % Less Than</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS		
BOILING POINT:	212 DEGREES F	
LBS/GAL:	10.3 - 10.7	
PH:	6 - 8	
SOLUBILITY IN WATER: DILUTABLE		
EVAPORATION RATE (nBuAc=1): SAME AS WATER		
VAPOR DENSITY (AIR=1): >1		
VAPOR PRESSURE, MM, HG AT 20 DEGREES C: SAME AS WATER		
PERCENT VOLATILE: 20 - 30 (BY WEIGHT)		
COLOR: LIGHT YELLOW PASTE	ODOR: MILD	

SECTION IV FIRE AND EXPLOSION HAZARD DATA

PRODUCT NAME: **TAYLOR 2020 WOOD MASTER ENGINEERED FLOOR ADHESIVE**
 ITEM NUMBER: 2020-4
 ITEM DESCRIPTION: Taylor 2020 Wood Master Engineered Floor Adh 4-Gal
 REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE:01/23/14 PRINT TIME:13:29

FLASH POINT, PENSKEY-MARTIN C.C.: NA
 AUTO IGNITION TEMPERATURE, DEGREES F: NA
 FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA
 EXTINGUISHING MEDIA:

(X) WATER SPRAY (X) CARBON DIOXIDE () OTHER
 (X) FOAM (X) DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:
 INHALATION:MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.
 EYES:VAPOR MAY CAUSE IRRITATION.
 SKIN:MAY CAUSE SLIGHT SKIN IRRITATION.
 INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

HEALTH EFFECTS OR RISK FROM EXPOSURE:
 ACUTE: MAY CAUSE MILD SKIN AND RESPIRATORY TRACT IRRITATION
 CHRONIC: NOT KNOWN

FIRST AID PROCEDURES:
 EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.
 SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.
 INHALATION: REMOVE TO FRESH AIR, ADMINISTER OXYGEN. IF NECESSARY, SEEK MEDICAL ATTENTION.
 INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VI REACTIVITY DATA

STABILITY: STABLE
 CONDITIONS TO AVOID: PROTECT FROM FREEZING.
 INCOMPATIBILITY (MATERIALS TO AVOID): OXIDIZING MATERIALS
 HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER, AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE
 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VII SPILL OR LEAK PROCEDURES

PRODUCT NAME: **TAYLOR 2020 WOOD MASTER ENGINEERED FLOOR ADHESIVE**
ITEM NUMBER: 2020-4
ITEM DESCRIPTION: Taylor 2020 Wood Master Engineered Floor Adh 4-Gal
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE:01/23/14 PRINT TIME:13:29

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED
KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.
RESPIRATORY PROTECTION: NIOSH RESPIRATOR IF ABOVE TLV
PROTECTIVE GLOVES: CHEMICAL RESISTANT GLOVES
EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD
OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.
WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.
OTHER HANDLING AND STORAGE REQUIREMENTS: PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL PLACE. KEEP AWAY FROM HEAT AND SPARKS.
PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES WHEN CLEANING ADHESIVE FROM EQUIPMENT.

SECTION IX SPECIAL PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED. AVOID BREATHING BUILDUP OF VAPORS. USE WITH ADEQUATE VENTILATION.
PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL DRY PLACE (50 - 90 DEGREES F). KEEP AWAY FROM HEAT AND SPARKS. KEEP FROM FREEZING.

SECTION X TOXICOLOGICAL PROPERTIES

INFORMATION BASED ON THE STATEMENT OF THE MANUFACTURER OF THE MAJOR POLYMER CONTAINED IN THIS PRODUCT.

ACUTE TOXICITY

ORAL TOXICITY: LD50/RAT - >2000 - 10000 MG /KG

SKIN IRRITATION

RABBIT: NON IRRITANT (OECD GUIDELINE 404)

EYE IRRITATION

RABBIT: NON IRRITANT (OECD GUIDELINE 405)

CHRONIC TOXICITY

OTHER INFORMATION:

NO ADVERSE HEALTH EFFECTS ARE EXPECTED IF HANDLED AS RECOMMENDED WITH SUITABLE PRECAUTION.

SECTION XI REGULATORY INFORMATION

PRODUCT NAME: **TAYLOR 2020 WOOD MASTER ENGINEERED FLOOR ADHESIVE**
ITEM NUMBER: 2020-4
ITEM DESCRIPTION: Taylor 2020 Wood Master Engineered Floor Adh 4-Gal
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE:01/23/14 PRINT TIME:13:29

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): NONE
SARA TITLE III SECTION 312 HAZARD CLASS: NONE
EPA SARA TITLE III SECTION 313: NONE

ALL COMPONENTS OF THIS PRODUCT ARE EITHER LISTED OR EXEMPT IN THE US EPA TSCA LIST

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE HARM.

SECTION XII SHIPPING DATA

D.O.T. PROPER SHIPPING NAME (49CFR172.101-102): NONE
HAZARDOUS SUBSTANCE(49CFR CERCLA LIST): NO RQ: N/A
D.O.T. HAZARD CLASSIFICATION (49CFR 172.101-102):
PRIMARY: NONE SECONDARY: NONE
D.O.T. LABELS REQUIRED (49CFR 172.101-102): NONE
D.O.T. PLACARDS REQUIRED (CFR 172.504): NONE
POISON CONSTITUENT (49CFR172.203(K)): NONE
BILL OF LADING DESCRIPTION: ADHESIVE CEMENT, NOI
UN/NA CODE: N/A

NOTICE

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.
